


UNI-TUGGER FAQs




Q What makes the UNI-Tugger so different from other mobile battery changers?

A The UNI-Tugger is able to change batteries with a wide variety of roll-out heights accommodating multiple lift trucks and applications simultaneously.



Q What makes adjustable roll-out so special?

A This ability to universally change forklift batteries means that distributors can hold the UNI-Tugger in stock and offer an 'off the shelf' solution with the possibility of providing equipment rentals.



Q Does flexible roll-out height offer any other benefits?

A A YES! The UNI-Tugger standardizes battery changing, which means no longer setting roller stands to the roll-out height of the battery, meaning one roller height can be used for all batteries.



Q What is the minimum and maximum roll-out height of the UNI-Tugger?

A The lowest roll-out height is 4.53" (115 mm), and the maximum roll-out height is 21.25" (540mm), assuming the host truck has a standard lift stroke of 4.72" (120mm).



Q How is the UNI-Tugger powered?

A An electrically powered pallet truck is permanently affixed to the UNI-Tugger, providing the power it needs to operate.

HAVE ADDITIONAL QUESTIONS? GET IN TOUCH

info@carneybatteryhandling.com
www.carneybatteryhandling.com

Tel: 1.905.564.0303
Toll free: 1.866.THE.BULL



Faqs



Q What is the required capacity of the host pallet truck?

A A suitable host pallet truck must accommodate the battery weight plus the self-weight of the Uni-Tugger. Consult your owners manual to ensure pallet truck compatibility.



Q Does the pallet truck require specific forks?

A NO! It doesn't, the UNI-Tugger will accommodate the forks of any standard pallet truck starting from 48" (1219mm) length and 22" (558mm) wide.



Q What type of warranty does the electromagnet have?

A Every CBH electromagnet comes with a 5-Year warranty. Visit our website to register your product for [warranty](#).



Q Can I customize the UNI-Tugger?

A YES! Specific options like 10 Pole magnets for heavy batteries (over 4,000 lbs /1,814 kg), Battery Guides for narrow batteries, Safety Gates and extended reach are all available add-ons. The UNI-Tugger is also available in a variety of colours.



Q Will the UNI-Tugger work with my forklift?

A The UNI-Tugger will work with any forklift from roll-out heights of 4.53" (115mm) to 21.25" (540mm). The battery should not exceed 49" (1,245mm) in length, 28" (711mm) in width for the 30" chassis and 34" (863mm) in width for the 36" chassis. The Maximum battery weight should not exceed 5,000lbs (2,268kg).

HAVE ADDITIONAL QUESTIONS? GET IN TOUCH

info@carneybatteryhandling.com
www.carneybatteryhandling.com

Tel: 1.905.564.0303
Toll free: 1.866.THE.BULL

